

## Rack Mounted Power Supply, 28 VAC—10 Amp

11/08

### Description

The **PS115** power supply provides 10 Amps of current for fixed and P/T/Z cameras. Power is provided to the CX452 card cage in the UTPLinks system for insertion and distribution of power and P/T/Z data. The number of fixed and/or P/T/Z cameras that can be powered by the PS115 is dependent upon the current requirements of the equipment being powered. The PS115 can be located at a mid-span position; i.e. IDF closet or at the “head-end”. These power supplies must be located in close proximity to the CX452.

### Features

- Power is provided to cameras and P/T/Z units in a closed, self-contained system
- PS115 units mount in a 19” rack
- Easy to install and configure
- Designed to be compatible with “Structured Cabling” standards
- Video, data and power can be run in the same Category 5 cable without interference



### Specifications

Size	1.75” H x 19.0” W x 8.6” D
Power Requirements	120 VAC
Output Voltage	28 VAC
Output Current	10 Amps
Enclosure Type	Standard 19” rack, 1 RU in height
Shipping Weight	21lbs

REV. 02182025

#### USA OFFICE:

729 1ST AVE N. BIRMINGHAM, AL 35203

PHONE : (847) 259-8900

E-MAIL: [INFO@NITEK.NET](mailto:INFO@NITEK.NET) • [WEB:NITEK.NET](http://WEB:NITEK.NET)