

Description


The **HD VH3239** video balun hub is a multi-channel video transceiver that provides a low cost means of sending quality live video over Category cabling. The HD VH3239 has been designed to meet the needs of the **HD TVI/CVI/AHD** cameras. The system can also adapt to existing communication and computer network spare pairs. The HD VH3239 can be used to transmit or receive video up to 750 feet when used with other products in the HD VB37 or HD VB39 family. The HD VH3239 is designed to provide superior immunity from noise and interference, such as RFI and EMI.

Features

- Works with any HD TVI/CVI/AHD or NTSC and PAL
- Built-in protection from power surges and transients
- Immunity to noise and interference
- Passive units—require no power
- Video & P/T/Z over a single pair with “up-the-coax” Systems when used with passive baluns
- Highly compact, only 1 RU in height
- Conveniently integrates with Nitek modular systems
- Video can be run in the same cable with telephone, computer signals and power

Design for use with

HD TVI / CVI / AHD



NITEK®

USA

5410 Newport Drive, # 24
 Rolling Meadows, IL 60008
 Phone: (847) 259-8900
 Fax: (847) 259-1300
 E-mail: info@nitek.net
 WWW.NITEK.NET

EUROPE

De Aar 99
 8253 PN Dronten
 The Netherlands
 Tel: +31(0) 321 310 043
 E-mail: info@nitekeurope.net
 WWW.NITEK.NET

TECHNICAL SPECIFICATION

32 Port Video Balun Hub

Size	1 RU x 6.0" D
Input	Standard BNC connector for 1 Vpp composite video Monochrome or Color
Video Format	HD TVI/CVI/AHD PAL, SECAM, NTSC, RS170, CCIR (Color or B/W)
Twisted Pair Connection	Screw terminals
Common Mode Rejection	>70dB
Operating Frequency	DC to 40 MHz
Recommended Transmission Distance	w/passive units—750 feet w/active units—3,000 feet
Wire Spec	26 to 18 AWG twisted pair
DC Loop Resistance	51 Ohms/1,000 feet
Nominal Capacitance	17pF/ft
Impedance	100 Ohms +/- 20%\
Category Wire	2 or better
Transient Immunity	Built-in

Wire and Cable Recommendations

We recommend using unshielded twisted pair wiring. The systems will operate over wire 26 to 18 AWG but are optimized for 24 AWG. Category cables may be used. Individually shielded pairs should be avoided, as they drastically reduce the operating range of the systems. Multi-pair cable with an overall shield is acceptable. Video can be operated in the same communication cable coexistent with telephone, computer, control signals, power voltages and other video signals. While video may be routed through telephone punch down block terminals, any bridge-taps, also called T-taps and any resistive, capacitive or inductive devices **MUST BE** removed from the pair.

